

Technical Datasheet Arbogrip TF

Arbogrip TF is a high strength, quick grab filling adhesive that bonds to a wide range of substrates. Arbogrip TF's gap filling and high bond strength properties make the product ideal for bonding to uneven surfaces, eliminating the need for battens.

Applications

Suitable for fixing wall panelling, dado rails, skirting boards, door surrounds, fascia boards, floor grippers, metal strips, laminates and veneers.

Arbogrip will bond together timber, brick, PVCu, metal, plywood, hardboard, insulation materials (not polystyrene), ceramics and a wide variety of other products. Suitable for interior and exterior use.

Application Instructions

Ensure that all joint surfaces are clean and free from contamination. Cut cartridge seal and fit nozzle. Cut nozzle to desired size. Extrude Arbogrip TF from the cartridge using an Arbo Caulking gun onto one of the substrates to be bonded. Align and press second substrate onto adhesive line. To achieve higher initial bond strength, substrates may be pulled apart after initial contact before pressing together again. Allow to cure for minimum of 24 hours before use.

Packaging

25 x 300ml Polyethylene Cartridges per box. Polyethylene Nozzles are included in each box.

Colours

Natural

Storage Life

9 months in original unopened packaging stored in a cool, dry place out of direct sunlight

Health and Safety.

Contains Solvents. Please consult Material Safety Data Sheet for full information.

Technical Data

Skin Time at 20° C/65 % RH: 3 -5 minutes

Application Temperature: +5° C to +40° C



Chemical Resistance: Resistant to most dilute acids and alkalis. Poor resistance to most organic solvents.

Accessories

Cleaners

Arbo Cleaner No.17- 1 Litre Tin (Xylene based – not suitable for use with plastics or delicate finishes)

Arbo Cleaner No. 16 - 1 Litre Tin (Alcohol Based)

Ancillary Equipment Polyethylene Nozzles Arbo Caulking Guns

Important: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

Adshead Ratcliffe, Derby Road, Belper, Derbyshire DE56 1WJ, England.

Telephone: 01773 826661

Fax: 01773 821215

Internet: www.arbo.co.uk