

UNDERLAY T22 Technik Line Hardwood Floors



15m²

100% RECYCLED IMPACT NOISE REDUCTION UNDERLAY

- Installed Directly under the Final Floor
- High Walking Comfort with Reduced Thickness
- High Durability and Long Term Resilience
- Aids Airborne Noise Insulation

PRODUCT DESCRIPTION
Recycled Rubber Underlay
for Impact Noise and Thermal
Insulation of Hardwood Floors.

THERMAL PROPERTIES
(ISO 8301)
Thermal Conductivity:
0,140 W/m[°]K
Thermal Resistance:
0,021 m²°K/W

**PHYSICAL AND MECHANICAL
PROPERTIES** (ISO 7322)
Specific weight: 650-750 Kg/m³
Tensile Strength: > 450 KPa
Compression: 20%
Recovery: > 90%
Durability: Lifetime of the Building

ACOUSTICAL RESULTS
(ISO 140 & 717)
 $\Delta L_w = 20\text{dB}$
(ITeCons ACU 128/10)

PACKAGING*
1m x 15m x 3mm
* Others sizes available upon request

UNDERLAY

T22

Technik Line

Hardwood Floors



100% RECYCLED IMPACT NOISE REDUCTION UNDERLAY

General installation instructions

The following installation instructions are recommended by Amorim Cork Composites, but are not intended as a definitive project specification. They are presented in an attempt to be used with recommended installation procedures of the flooring manufacturers.

Room conditions

Temperature > 10°C / Room moisture content < 75%.

Subfloor

All subfloor work should be structurally sound, clear and level. The moisture content of the subfloor should not be more than 2.5% (CM) by weight measured on concrete subfloors.

Perimeter insulation barrier

Install a perimeter insulation barrier minimum 35mm wide vertically around the entire perimeter of the room. This is highly recommended in order to avoid lateral propagation of impact noise. Spot adhere the strips to the wall using acrylic glue or a bead of silicone sealant (do not forget the edges of pipes, ducts, etc). Before the installation of the skirting boards, the insulation strips must be leveled (trimmed) to the height of the wood.

Installations instructions for AcoustiCORK T22

Unpack the AcoustiCORK T22 at least 24h before the installation and store it in the room where the installation will take place. Use a properly sized V-notched trowel and acrylic glue to glue the AcoustiCORK T22 to the concrete slab. Always follow the glue manufacturers recommended instructions.

Cut the AcoustiCORK T22 to the desired length and install directly over the subfloor with crown of the rolled materials up, removing all trapped air. Butt the AcoustiCORK T22 directly against the insulation perimeter barrier already installed. Put the loose laid material back. Using a properly sized V-notched trowel, apply acrylic glue to the concrete slab. Gently, return the pulled back material to its measure place and roll in both directions with a roller. Proceed to cover the entire floor making sure that the joints are butted tight. After completion, the AcoustiCORK T22 should cover the entire flooring area without gaps and with joints securely taped.

Final flooring

Use polyurethane based adhesive. Always follow manufacturers recommended installation instructions.

Important notes

Never mechanically fasten the AcoustiCORK T22 to the flooring floor as this will severely diminish its acoustical value.

For detailed installation instructions, please contact us.